











Fittings for ABS/SWP Pipe

	Victaulic Adapter	S/W	2" - 12"	Solvent Weld direct to pipe in order to use Victaulic fittings
	IPS/SWP Sleeve	S/W	2" - 8"	To size pipe to IPS Fittings
	Coupling	S/W	2" - 12"	Joining pipe
	90° STD Elbow	S/W or Victaulic End	2" - 12"	8" and larger sizes are fabricated and fiberglass wrapped plain end or vic end only
	45° STD Elbow	S/W or Victaulic End	2" - 12"	8" and larger sizes are fabricated and fiberglass wrapped plain end or vic end only
	Tee	S/W or Victaulic End	2" - 12"	8" and larger sizes are fabricated and fiberglass wrapped plain end or vic end only
	90° Sweep Elbow	Plain End or Victaulic End	2" - 12"	Long radius for maximum wear, 36" radius up to 6", 60" radius for 8", 96" radius for 10" and 12" pipe
	45° Sweep Elbow	Plain End or Victaulic End	2" - 12"	Long radius for maximum wear, 36" radius up to 6", 60" radius for 8", 96" radius for 10" and 12" pipe
	45° Lateral Wye	S/W or Victaulic End	2" - 12"	8" and larger sizes are fabricated and fiberglass wrapped plain end or vic end only
	Flange	S/W	2" - 12"	

- Some fittings are supplied with PVC body.
- Other configurations of fittings can be fabricated. Call factory for availability and quotation.